

Mini temperature switch, flameproof enclosure Ex d

07/2016

Applications

- Temperature monitoring and control of processes
- Safety-critical applications in general process instrumentation, especially in the chemical and petrochemical industries, oil and gas industries, power generation incl. nuclear power plants, water/wastewater industries, mining
- For measuring points with limited space, e.g. control panels

Special features

- No power supply needed for switching of electrical loads
- Setting ranges from -15 ... +20 °C to 180 ... +250 °C
- Repeatability of the set point ≤ 1 % span
- 1 set point, SPDT, high switching power up to AC 250 V, 5 A
- Direct mounting or remote mounting with capillary ≤ 10 m



Order numbers

Case	stainless steel 316L	
Sensor	direct mounting	remote mounting with capillary, length 2 m
Process connection	1/2 NPT male	
Electrical connection	1/2-14 NPT-M, with 1,5 m cable	
Electric contacts	1xSPDT, silver contact, hermetically sealed	
Setting range		
-15 ... +20 °C	14174219	14174220
5 ... 70 °C	14174222	14174225
55 ... 140 °C	14174226	14174227
130 ... 190 °C	14174253	14174255
180 ... 250 °C	14174256	14174257

Legend: available from stock in Germany available after production **** not available

Quick order code (for further details see data sheet TV 31.72)

Field no.	Code	Version
sensor version		
①	B	direct mounting
	C	remote mounting with capillary, length 2 m
	Q	remote mounting with capillary, length 5 m
	R	remote mounting with capillary, length 10 m
contact version		
②	E	1xSPDT, silver contact, hermetically sealed
	J	1xSPDT, gold-plated contact, hermetically sealed
setting range		
③	CCA	-15 ... +20 °C, working range -40 ... +50 °C, proof temperature +70 °C
	CCB	5 ... 70 °C, working range -40 ... +95 °C, proof temperature +120 °C
	CCC	55 ... 140 °C, working range -40 ... +160 °C, proof temperature +190 °C
	CCD	130 ... 190 °C, working range -40 ... +215 °C, proof temperature +230 °C
	CCE	180 ... 250 °C, working range -40 ... +300 °C, proof temperature +330 °C
process connection		
④	E	1/2 NPT male
	F	3/4 NPT male
	G	G 1/2 A male
	H	G 3/4 A male
	C	helical bulb, including wall mounting plate
electrical connection		
⑤	M	1/2-14 NPT-M, with 1,5 m cable
	S	1/2-14 NPT-M, with 3 m cable
	T	1/2-14 NPT-M, with 5 m cable
	N	Adapter 1/2-14 NPT-F, with 1,5 m cable
	O	Adapter 3/4-11 NPT-F, with 1,5 m cable
	R	Adaptor M20x1,5-F, with 1,5 m cable
	P	Adapter M20x1,5-M, with 1,5 m cable
Q	Terminal box, aluminium alloy, with 3 connections 1/2 NPT female	
Mounting		
⑥	A	direct mounting
	B	Wall mounting plate
	Y	Yoke for 2" pipe mounting
Special design features		
⑦	N	NACE
	A	Grounding cable cross-section: max. 4 mm ²
	Z	without
ambient condition / application condition		
⑧	O1	Offshore
	ZZ	without

Order code: TXA4 - B-

Please specify approvals and certificates via free text.

C5 Flameproof Ex d IECEx-ATEX
C4 SIL 2 for functional safety

© 2016 WIKA Alexander Wiegand SE & Co. KG, all rights reserved.
The specifications given in this document represent the state of engineering at the time of publishing.
We reserve the right to make modifications to the specifications and materials.